


AMON WALL A/M




Part number	306311
Lampholder:	LED
Light Source:	LED
Wattage:	28 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK08 5J xx5
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Asymmetric medium reflector
Lightsource lumen output:	3120 lm
Luminaire lumen output:	1811 lm
L:	L70
B:	B10
Lifetime:	80000 h
Ta MIN luminaire:	-25°
Ta MAX luminaire:	35°
ULR:	0%



Description

- Wall-mounted LED luminaire, comprising:
- Extruded aluminium profile housing, painted ISO 9227
 - Extra-clear, tempered, flat glass diffuser, screen-printed inside
 - High-transparency polycarbonate lenses grant an optimized light transmission
 - Anti-ageing silicone gasket
 - Painted die cast aluminium trims and caps
 - Built-in driver
 - Aluminium heat sink
 - Stainless steel external screws
 - Painted die cast aluminium bracket for wall mounted (WALL) applications, for easy installation
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

